

EFL2503-HV-12

HIGH CAPACITY ELECTRIC COUNTERBALANCED FORKLIFT 25T

25000 kg 4000 mm 618.24 V Li-Ion



With its 618V high-voltage Li-ion system and robust 135 kW PMSM motor, the EFL2503-HV sets a new standard in the high-capacity forklift segment. Capable of lifting 25,000 kg at a 1,200 mm load center, it combines diesel-like power with electric precision. Designed for maximum uptime, the truck features advanced thermal management, high-grade hydraulics, and a full AC cabin for operator comfort and safety.

| SPECIFICATION | REF | UNIT | VALUE |
|---|-----------|------|--------------|
| Battery type | | | Li-Ion |
| Battery nominal capacity | | Ah | 456 |
| Battery voltage | | V | 618.24 |
| Load capacity | Q | kg | 25000 |
| Load centre distance | c | mm | 1200 |
| Service weight | | kg | 38700 |
| Retracted mast height | h_1 | mm | 3950 |
| Lift height | h_3 | mm | 4000 |
| Height, mast extended | h_4 | mm | 5890 |
| Overall length | | mm | 8860 |
| Overall width | b_1/b_2 | mm | 3080 |
| Length to face of forks | I_2 | mm | 6420 |
| Fork dimensions | s/e/l | mm | 110/250/2400 |
| Turning radius | | Wa | 6350 |
| Operator type | | | Seated |
| Load distance, centre of drive axle to fork | | mm | 1130 |

Features

High Performance: High speed and high gradeability

High-voltage Li-ion batteries enable more power delivery to motors, improving acceleration and travel speeds for high-capacity trucks. PMSMs complement this with rapid response times, swiftly reaching required speeds and torques. This combination of PMSM and high voltage can provide stable and strong power output, which further gives high-capacity trucks excellent climbing capabilities ensuring that the forklift can cope with various applications with ease.

The high-voltage model offers a 1.5-2 times performance improvement over the low-voltage model. Taking the 10-ton model as an example:

100% improvement in travel speed for high voltage models in laden and unladen conditions.

The high-voltage model demonstrates a 45% faster lifting speed.

100% improvement in gradeability when unladen, 45% improvement when laden for high voltage models.

Energy Efficiency: extended runtime and fast charging

High-voltage Li-ion batteries have high energy density and can store more electrical energy within a compact volume. High-voltage systems consume less energy and provide longer battery running time comparing low-voltage systems. Notably, these high-voltage Li-ion batteries boast an impressive cycle life of up to 4000 cycles, ensuring long-term durability and minimizing the need for battery replacements.

The PMSMs incorporate advanced control technology to optimize motor efficiency. Unlike traditional AC motors, PMSMs have higher energy conversion efficiency and reduce energy waste. This means that high-capacity trucks can work continuously for prolonged hours at lower costs.

Equipped with fast charging capabilities, high-capacity trucks offer a remarkable charging experience. The high-voltage models are compatible with vehicle-grade charging stations and support 1C charging rating, allowing them to be fully charged in as fast as 1-1.2 hours. This minimizes downtime and maximizes productivity, making it ideal for multi-shift operations

Lithium batteries present considerably lower charging costs than fuel expenses. The integration of high-voltage and PMSM technology achieves up to 15% greater electricity savings versus traditional lithium and AC technology configurations. This significantly reduces long-term energy consumption costs.



Safety Assured: Battery, motor protection, monitoring and mast buffering

Both high-voltage lithium batteries and PMSM employ multiple protective measures to ensure safe operations including overcharge protection, over-temperature monitoring, short-circuit protection, etc. minimizing the risk of potential hazards and maximizing operational safety.

The central controlling module- VCU (Vehicle Control Unit) extends the safety of the high-voltage forklifts. VCU provides precise control and real-time monitoring of critical parameters to ensure the truck operates within safe limits.

It also features turn speed control, which adjusts the forklift's speed based on the turning angle, ensuring stability during turns. An over-speed alarm alerts the operator if the forklift exceeds the safe speed limit.*

The high-capacity forklift mast is equipped with a hydraulic buffering system that ensures smooth lifting and lowering of loads. With controlled deceleration, the fork movement is smooth with no abrupt stops that could damage the load or cause operator discomfort. This feature enhances operational safety and prolongs the lifespan of the mast components.




Smart and reliable strategy for thermal management

The high-capacity trucks utilize three distinct cooling systems to ensure optimal performance and reliability. Specifically, two water cooling systems are employed for the motor and the battery, while an oil cooling system is dedicated to the hydraulics system.

The water cooling systems provide superior cooling performance, preventing the truck from overheating even under the most demanding conditions or in the heat of summer. Water's higher heat transfer capacity compared to air allows it to dissipate heat more efficiently from critical components like the motor and battery. This efficient heat dissipation helps maintain the battery temperature around 30~35 °C , protecting these vital components from overheating and potential damage or failure. Consequently, this enhances the overall reliability and longevity of the high-capacity trucks.

Additionally, water cooling systems typically operate with less noise compared to air cooling systems that rely on high-speed fans. This noise reduction is particularly beneficial in applications where a quieter operation is desirable, such as in urban areas or indoor facilities.

The oil cooling system, on the other hand, is used for the hydraulics system. This system ensures that the hydraulic components remain within optimal temperature ranges, thereby maintaining their efficiency and preventing overheating. By effectively managing the temperature of the hydraulics system, the oil cooling system contributes to the smooth and reliable operation of the truck's hydraulic functions.





Low maintenance: Longer battery life span

Operating at a higher voltage allows the battery to be designed with fewer individual cells. With fewer components and a simpler design, the risk of battery failure is lowered.

Thanks to advanced BMS (Battery Management System) which helps to regulate and monitor high-voltage battery, these batteries tend to have a longer life than low-voltage lithium batteries, reducing the need of battery replacement.

The brushless, simple rotor design of PMSM eliminates mechanical wear from brushes and commutators. This durable, low-friction construction requires minimal periodic maintenance, reducing associated labor costs and downtime.



Sustainability : Zero emissions for cleaner environment

As fully electric trucks powered by lithium-ion batteries, these forklifts produce zero emissions during operation, eliminating exposure to toxic fumes like carbon monoxide and nitrogen oxides. Unlike lead-acid batteries which can leak corrosive acid, lithium-ion batteries do not risk hazardous spills. The high-capacity li-ion trucks contribute to a cleaner and safer indoor working environment without compromising handling capabilities.

Strong adaptability adaptable to harsh outdoor weather conditions

Experience uninterrupted productivity through rain, puddles, and damp conditions with the overall IPX4 rating. Plus an exceptional IP67 rating for high-voltage components. Engineered to withstand harsh temperature, high-capacity trucks offer an ambient temperature range of -20 °C ~40 °C allowing them to perform no matter climate.

Battery heating when charging comes as a standard function for high capacity models, which is activated when the surrounding temperature is below zero to always offer an optimal temperature range for efficient and safe charging even in cold weather conditions.



The dual front wheels is a standard configuration on several models offering a wider base of support, which greatly improves the forklift's stability. Considering the capacity loads of the high-capacity trucks, the weight of the load is more evenly distributed across a larger surface area. The increased ground contact area provided by the dual wheels enhances traction. This is particularly beneficial in environments where the floor may be slippery or uneven while operating outdoors, ensuring that the forklift can maintain a firm grip and operate safely. This not only helps in maintaining balance but also minimizes the stress on individual tires, extending the lifespan of the tires.

Great support for clients' investment: After-sales Service

Remote/Online Services:

Telematics technology enables remote monitoring of battery conditions, performance status, and other critical parameters for forklifts. Additionally, production, technical, and after-sales experts are available around the clock to provide prompt and comprehensive solutions for any maintenance issues through virtual support.

Physical Services:


Comprehensive manuals and supporting documents are provided for all forklift models. In case of breakdowns or replacements, spare parts are swiftly delivered to the clients' locations by global subsidiaries or domestic inventory, minimizing operational disruptions caused by equipment downtime.

VDI Chart

| SPECIFICATION | REF | UNIT | VALUE |
|---------------|---------------|------|--------|
| 1.4 | Operator type | | Seated |

| | SPECIFICATION | REF | UNIT | VALUE |
|--------|---|--------------------------------|------|---------------|
| 1.5 | Load capacity | Q | kg | 25000 |
| 1.6 | Load centre distance | c | mm | 1200 |
| 1.8 | Load distance, centre of drive axle to fork | | mm | 1130 |
| 1.9 | Wheelbase | | mm | 4300 |
| 2.1 | Service weight | | kg | 38700 |
| 2.2 | Axle loading, laden front/rear | | kg | 57800/5900 |
| 2.3 | Axle loading, unladen front/rear | | kg | 18900/19800 |
| 3.1 | Tyre type | | | Pneumatic |
| 3.2 | Tyre size, front | | | 14.00-24-28PR |
| 3.3 | Tyre size, rear | | | 14.00-24-28PR |
| 3.5 | Wheels, number front/rear (x=drive wheels) | | | 4x/2 |
| 3.6 | Tread width, front | b ₁₀ | mm | 2200 |
| 3.7 | Tread width, rear | b ₁₁ | mm | 2460 |
| 4.1 | Tilt of mast/fork carriage forward/backward | | ° | 6/10 |
| 4.12 | Tow coupling height | | mm | 390 |
| 4.19 | Overall length | | mm | 8860 |
| 4.2 | Retracted mast height | h ₁ | mm | 3950 |
| 4.20 | Length to face of forks | I ₂ | mm | 6420 |
| 4.21 | Overall width | b ₁ /b ₂ | mm | 3080 |
| 4.22 | Fork dimensions | s/e/l | mm | 110/250/2400 |
| 4.23 | A,B Fork carriage class/type A, B | | | - |
| 4.24 | Fork carriage width | | mm | 3080 |
| 4.3 | Free lift | | mm | 125 |
| 4.31 | Ground clearance, laden, below mast | | mm | 220 |
| 4.32 | Ground clearance, centre of wheelbase | | mm | 370 |
| 4.34.1 | Aisle width for pallets 1000×1200 crossways | | Ast | 10120 |
| 4.34.2 | Aisle width for pallets 800×1200 lengthways | | Ast | 10120 |
| 4.35 | Turning radius | | Wa | 6350 |
| 4.4 | Lift height | h ₃ | mm | 4000 |
| 4.4.1 | Max lift height | | mm | 7000 |
| 4.5 | Height, mast extended | h ₄ | mm | 5890 |
| 4.7 | Height of overhead guard (cabin) | | mm | 3380 |
| 4.8 | Seat height/standing height | | mm | 2465 |
| 5.1 | Travel speed, laden/unladen | | km/h | 22/22 |

| | SPECIFICATION | REF | UNIT | VALUE |
|-------|--|-----|-------|---------------|
| 5.10 | Service brake | | | Hydraulic |
| 5.11 | Parking brake | | | Hydraulic |
| 5.2 | Lifting speed, laden/unladen | | m/s | 0./0.35 |
| 5.3 | Lowering speed, laden/unladen | | m/s | 0.48/0.4 |
| 5.5 | Drawbar pull, laden/unladen | | | 140000/140000 |
| 5.6 | Max. drawbar pull, laden/unladen | | | 160000/160000 |
| 5.8 | Max. gradeability, laden/unladen | | % | 20/30 |
| 6.1 | Drive motor rating S2 60 min | | kW | 135 |
| 6.2 | Lift motor rating at S3 15% | | kW | 90 |
| 6.4 | Battery nominal capacity | | Ah | 456 |
| 6.4 | Battery voltage | | V | 618.24 |
| 6.4.1 | Battery type | | | Li-Ion |
| 6.5 | Battery weight | | kg | 1864 |
| 6.5 | Charger output current | | | 115 |
| 6.6 | Energy consumption according to DIN EN 16796 | | kWh/h | 26 |
| 6.7 | Turnover output according to VDI 2198 | | | / |
| 6.8 | Turnover efficiency according to VDI 2198 | | | / |
| 8.1 | Type of drive control | | | PMSM |
| 10.5 | Steering design | | | Hydraulic |
| 10.7 | Sound pressure level at the drivers ear | | dB(A) | <75 |



RATED CAPACITIES AND LOAD CENTERES GRAPH



Mast Options

| MAST TYPE | LIFT HEIGHT (H3, MM) | MAST LOWERED HEIGHT (H1, MM) | MAST EXTENDED HEIGHT, NO BACKREST (H4, MM) | MAST EXTENDED HEIGHT, WITH BACKREST (H4, MM) | FREE LIFT HEIGHT, NO BACKREST (H2, MM) | FREE LIFT HEIGHT, WITH BACKREST (H2, MM) |
|-----------------|----------------------|------------------------------|--|--|--|--|
| 2-Standard Mast | 4000 | 3950 | 5890 | 5890 | 125 | 125 |

Options

| ITEM | OPTIONS (optional items marked in yellow) |
|---------------------------------|--|
| Fork dimension | 12500*1200, 5A, 250*110*2440 12500*1200, 5A, 300*120*2440 |
| Fork lowered height | 125 |
| Fork carriage width option | 3080 |
| Load wheel type | Double |
| Seat type | Suspension + safety belt logic switch |
| Attachments | Adjustable fork |
| Safe hook | No |
| Traction pin | Yes and not customized |
| Electrostatic chain | No |
| Handle head type | One-handed big handle head |
| Load wheel material | Rubber |
| Drive wheel material | Rubber |
| Front wheel type | Double |
| Front wheel material | Pneumatic Solid |
| Rear wheel material | Pneumatic Solid |
| Battery capacity | 614.4V/460Ah |
| Charger | 200V-750V/60KW External (national standard) 300V-1000V/80KW External (national standard) 200V-750V/20KW External (European standard) |
| Battery display indicator (BDI) | With time |
| Area warning lamp | Yes and not customized |
| Rearview mirror | Yes and not customized |
| Buzzer | Yes and not customized |
| Camera | Yes and not customized |

| ITEM | OPTIONS (optional items marked in yellow) |
|--|--|
| Fire extinguisher | Yes and not customized |
| Vertical handler working | No |
| OPS system | Yes and not customized |
| Guide wheel | No |
| USB interface | Yes and not customized |
| Telematics | No Yes and not customized |
| The British standard cannot walk when charged | Yes and not customized |
| Castor wheels | No |
| Water auto-filling system | No |
| Front lamp | LED |
| Rear lamp | LED |
| Warning lamp | Yes and not customized |
| Steering lamp | LED |
| Blue lamp | Yes and not customized |
| Battery side pull function | No |
| Cold storage | No |
| Cabin | Fully enclosed cabin;front, rear and top wipers; With electric fan;Heating and cooling air conditioning system |
| Proportional lift system | Yes and not customized |
| Forks tilt forward and backward | Yes and not customized |
| Overhead guard | Yes and not customized |
| Battery side pull attachment | No |
| Turn speed control | Yes |
| Heating system during lithium battery charging | Yes |